Prolog

- Prolog: 'Programmation en Logique'
- 1974 - R.A. Kowalski: 'Predicate logic as a programming language', Proc IFIP 1974, pp. 569-574:
  - First-order predicate logic for the specification of data and relationships
  - Computation = logical deduction
- 1972 - A. Colmerauer, P. Roussel: first Prolog-like interpreter

Logic Programming (LP)

- R.A. Kowalski (Imperial College):

  Algorithm = Logic + Control

- Imperative languages (C++, Java):
  - data (what)
  - operations on data (how)
  - no separation between 'what' and 'how'

LP: Logic + Control

what → Logical Formulas

$\forall x\,(P(x) \rightarrow Q(x))$

how → Logical Deduction

$$\frac{\neg\psi,\ \varphi \rightarrow \psi}{\neg\varphi}$$

What: Problem Description

- *Horn clause:* $A \leftarrow B_1, B_2, \ldots, B_n$
- Equivalent to: $A \vee \neg B_1 \vee \neg B_2 \vee \ldots \vee \neg B_n$
- Meaning: A is true if
  - B_1 is true, and
  - B_2 is true, ..., and
  - B_n is true

What: Problem Description

$A \leftarrow B_1, \ldots, B_n$

- specification of **facts** concerning *objects* and *relations* between objects
- specification of **rules** concerning *objects* and *relations* between objects
- specification of **queries** concerning *objects* and *relations*

Problem Description

- Facts: $A \leftarrow$
- Rules: $A \leftarrow B_1,\ldots,B_n$
- Queries: $\leftarrow B_1,\ldots,B_n$

Meet the Royal Family

Example: Family Relations

- Facts: mother(juliana, beatrix) ←
  (constant)
- Rules:
  parent(X, Y) ← mother(X, Y)
  parent(X, Y) ← father(X, Y)
  (variable)
- Query: ← parent(juliana, beatrix)

Logic Program

mother(juliana, beatrix) ←
mother(beatrix, alexander) ←
father(claus, alexander) ←

parent(X, Y) ← mother(X, Y)
parent(X, Y) ← father(X, Y)

- Queries:
  ← parent(claus, alexander)
  ← parent(beatrix, juliana)

Prolog

- Prolog: practical realisation of LP
- Prolog clause:

  A :- B_1, B_2, …, B_n.
  head: A — body: B_1, B_2, …, B_n

- Example:

```
mother(juliana, beatrix).
parent(X, Y) :-
    mother(X,Y).
:- parent(juliana, beatrix).
```

Why is Prolog so Handy?

Hotel suite design:





1. Living-room window opposite the front door
2. Bed-room door at right angle with front door
3. Bed-room window adjacent to wall with bed-room door
4. Bed-room window should face East

C-like

```
type dir = (north, south, east, west);
livrm(fd, lw, bd : dir) : boolean;
{
   livrm = opposite(fd, lw) and adjacent(fd, bd)
}
bedrm(bd, bw : dir) : boolean;
{
   bedrm = adjacent(bd, bw) and (bw = east)
}
suite(fd, lw, bd, bw : dir) : boolean;
{
   suite = livrm(fd, lw, bd) and bedrm(bd, bw)
}
```

Continued

```
for  fd = north to west do
     for lw = north to west do
          for bd = north to west do
               for bw = north to west do
                    if suite(fd, lw, bd, bw) then
                         print(fd, lw, bd, bw)
```

In Prolog

```
livrm(Fd, Bd, Lw) :-
   opposite(Fd, Lw), adjacent(Fd, Bd).
bedrm(Bd, Bw) :-
   adjacent(Bd, Bw), Bw = east.
suite(Fd, Lw, Bd, Be) :-
   livrm(Fd, Lw, Bd), bedrm(Bd, Bw).

:- suite(Fd, Lw, Bd, Bw).
```

Declarative Semantics

- Prolog clause: A :- $B_1, B_2, \ldots, B_n$.
- *Meaning*: A is true if
  - B_1 is true, and
  - B_2 is true, …., and
  - B_n is true

Procedural Semantics

- Prolog as a procedural language
- Prolog clause = **procedure**

A :- B_1, B_2, …, B_n.

procedure head

procedure body

- Query = procedure **call**

:- B_1, B_2, …, B_n.

More General Programs

- Use often lists:

  [a, b, c , d] = [a | [b, c, d]]

  head tail

- Element is first element (fact):

  member(a, [a | [b, c, d]]).

- In general:

  member(X, [X|_]).

Set Membership

member(X, [X|_]).
member(X, [_|Y]) :-
    member(X, Y)

- Queries:

  :- member(a,[b,a,c])

  :- member(d,[b,a,c])

Example 1

/*1*/ member(X, [X|_]). procedure entry
/*2*/ member(X, [_|Y]) :- procedure entry
    member(X, Y).
/*3*/ :- member(a, [a, b, c]). call

Step 1

:- member(a, [a, b, c]).
/*1*/ member(X, [X|_]).

Instantiation: X = a *match* with /*1*/

Example 2

/*1*/ member(X, [X|_]). procedure entry
/*2*/ member(X, [_|Y]) :- procedure entry
    member(X, Y).
/*3*/ :- member(a, [b, a, c]). call

Step 1

:- member(a, [b, a, c]).
/*1*/ member(X, [X|_]).

Instantiation: X = a *no match* with /*1*/

Example 2 (continued)

/*1*/ member(X, [X|_]). procedure entry
/*2*/ member(X, [_|Y]) :- procedure entry
    member(X, Y).
/*3*/ :- member(a, [b,a,c]). call

Step 2

:- member(a, [b, a, c]).
/*2*/ member(X, [_|Y]) :- member(X, Y).

Match: X = a; Y = [a, c]

Example 2 (continued)

/*1*/ member(X, [X|_]). procedure entry
/*2*/ member(X, [_|Y]) :- procedure entry
    member(X, Y).
/*3*/ :- member(a, [b,a,c]). call

Step 3

:- member(a, [a, c]). subcall
/*1*/ member(X, [X|_]).

Match: X = a

Matching

- A call and procedure head match if:
  - predicate symbols are equal
  - arguments in corresponding positions are equal
- Example:

```
        :- member(a, [a, c]).
/*1*/  member(a, [a|_]).
```

Variables & Atoms

```
mother(juliana, beatrix).
```

Calls:

```
:- mother(X, Y).
   X = juliana
   Y = beatrix

:- mother(_, _).    /* anonymous variable */
yes

:- mother(juliana, juliana).
no
```

Left-right Selection Rule

```
q.
r.
s.
p :- q, r, s.
```

Call:

```
:- p.
:- q, r, s.
:- r, s.
:- s.
```

Top-bottom Selection Rule

```
p(a).
p(b).
p(c).
p(X) :- q(X).
q(d).
q(e).
```

Call:

```
:- p(Y).
Y = a;
Y = b;
Y = c;
Y = d;
Y = e;
no
```

Backtracking

Backtracking: systematic search for alternatives

Example: search for paths in tree *T*



Backtracking




```
branch(a, b).
branch(a, c).
branch(c, d).
branch(c, e).
path(X, X).
path(X, Y) :-
    branch(X,Z), path(Z,Y).
```

Backtracking




```
branch(a, b).
branch(a, c).
branch(c, d).
branch(c, e).
path(X, X).
path(X, Y) :-
    branch(X, Z), path(Z, Y).
```

```
:- path(a, d).    /* query */
path(a, d) :- branch(a, Z), path (Z, d).
```

1 → branch(a, Z) → 1

1 ← Z = b, branch(a, b).

Backtracking




```
branch(a, b).
branch(a, c).
branch(c, d).
branch(c, e).
path(X, X).
path(X, Y) :-
    branch(X, Z), path(Z, Y).
```

```
:- path(a, d).    /* query */
path(a, d) :- branch(a, Z), path (Z, d).
```

2 → Z = b, path(b, d) → 2

2 ← X = b, Y = d

```
path(b, d) :- branch(b, Z'), path(Z', d).
```

Backtracking




```
branch(a, b).
branch(a, c).
branch(c, d).
branch(c, e).
path(X, X).
path(X, Y) :-
    branch(X, Z), path(Z, Y).
```

```
path(b, d) :- branch(b, Z'), path(Z', d).
```

3 → branch(b, Z') → 3

backtrack

Backtrack Point




```
branch(a, b).
branch(a, c).
branch(c, d).
branch(c, e).
path(X, X).
path(X, Y) :-
    branch(X, Z), path(Z, Y).
```

```
:- path(a, d).    /* query */
path(a, d) :- branch(a, Z), path (Z, d).
```

1′ → branch(a, Z) → 1′

1′ ← Z = c, branch(a, c).

Backtracking




```
branch(a, b).
branch(a, c).
branch(c, d).
branch(c, e).
path(X, X).
path(X, Y) :-
    branch(X, Z), path(Z, Y).
```

```
:- path(a, d).    /* query */
path(a, d) :- branch(a, Z), path (Z, d).
```

2′ → Z = c, path(c, d) → 2′

2′ ← X = c, Y = d

```
path(c, d) :- branch(c, Z'), path(Z', d).
```

Backtracking




```
branch(a, b).
branch(a, c).
branch(c, d).
branch(c, e).
path(X, X).
path(X, Y) :-
    branch(X, Z), path(Z, Y).
```

```
path(c, d) :- branch(c, Z'), path(Z', d).
```

3′ → branch(c, Z') → 3′

Z′ = d, branch(c, d)

Backtracking




```
branch(a, b).
branch(a, c).
branch(c, d).
branch(c, e).
path(X, X).
path(X, Y) :-
    branch(X, Z), path(Z, Y).
```

```
path(c, d) :- branch(c, Z'), path(Z', d).
                              Z' = d        4
                              path(d, d)
4                             X = d
                              path(d, d)
```

Terminology

- From programming languages (Prolog as procedural language):

```
nat(0).
nat(s(X)) :- nat(X).
```

  - term: nat(0), nat(s(X)), nat(X), :-(nat(s(X)), nat(X)), s(X), 0, X
  - functor: s, nat, :-
  - principal functor: nat in nat(s(X)), :- in :-(nat(s(X)), nat(X)), s in s(X)
  - number: 0
  - variable: X

Inversion of Computation (1)

- **Example:** concatenation of lists
  U = V ° W
  with U, V, W lists and ° concatenation operator
- Usage:
  - [a, b] = [a] ° **W** ⇒ **W** = [b]
  - [a, b] = **V** ° [b] ⇒ **V** = [a]
  - **U** = [a] ° [b] ⇒ **U** = [a, b]
  - [a, b] = **V ° W?**

Inversion of Computation (2)

- Prolog concatenation of lists:

```
concat([], U, U).
concat([X|U], V, [X|W]) :-
    concat(U, V, W).
```

- concat as constructor:

```
?- concat([a, b], [c, d], X).
   X = [a, b, c, d]
```

- concat used for decomposition:

```
?- concat(X, Y, [a, b, c, d]).
   X = []
   Y = [a, b, c, d]
```

Inversion of Computation (3)

- concat used for decomposition:

```
?- concat(X, Y, [a, b, c, d]).
   X = []
   Y = [a, b, c, d];
   X = [a]
   Y = [b, c, d];
   X = [a, b]
   Y = [c, d];

   ...
```

Order of Clauses (1)

- LP: order is irrelevant
- Prolog: order may be relevant
- Example:

```
member(X,[_|Y]) :-
    member(X,Y).
member(X,[X|_]).
:- member(a,[b,a,c]).
```

Order of Clauses (2)

```
/*1*/  member(X, [_|Y]) :-
           member(X, Y).
/*2*/  member(X, [X|_]).
```

```
?- member(a, [a,b]).
   X = a, Y = [b]            match with 1
   ?- member(a, [b]).        next call
      X' = a, Y' = []        match with 1
      ?- member(a, []).      fail 1 and 2
   fail 1 and 2
   fail 1, backtracking to 2
   X = a                     match 2
yes! (but not efficient)
```

Order of Clauses (3)

```
/*1*/  member(X, [_|Y]) :-
           member(X, Y).
/*2*/  member(X, [X|_]).
```

```
?- member(X, [a, b]).
   X' = X, Y = [b]           match with 1
   ?- member(X', [b]).       next call
      X'' = X', Y' = []      match with 1
      ?- member(X'', []).    fail 1 and 2
   X'  = b                   fail 1, match 2
   X = b;                    backtracking
   X = a                     match 2
yes! (but not efficient)
```

Order of Clauses (4)

```
/*1*/  member(X, [_|Y]) :-
           member(X, Y).
/*2*/  member(X, [X|_]).
```

```
?- member(a, Z).
   X = a, Z = [_|Y]          match 1
   ?- member(a, Y).          next call
      X' = a, Y= [_|Y']      match 1
      ?- member(a, Y').      next call
            :
            :
```

Stack overflow

Conclusions Order of Clauses

- LP: order clauses is irrelevant
- Prolog:
  - Order has effect on efficiency of program
  - Order may affect termination: terminating program + order change ≠ terminating program

Order of Conditions (1)

- Length of list with successor function $s : N \rightarrow N$, with $s(x) = x + 1$
- Program:

```
/*1*/ length([], 0).
/*2*/ length([_|X], N) :-
         length(X, M),
         N = s(M).
```

- Use:

```
?- length([a, b], N).
N = s(s(0))
```

Order of Conditions (2)

- Program:

```
/*1*/ length([], 0).
/*2*/ length([_|X], N) :-
         length(X, M),
         N = s(M).
```

- Use:

```
?- length(L, s(0)).
L = [_A];
```

Stack overflow

Order of Conditions (3)

```
/*1*/ length([], 0).
/*2*/ length([_|X], N) :-
        length(X, M),
        N = s(M).
```

- Trace:

```
?- length(L, s(0)).
   L = [_A|X], N = s(0)            match 2
   ?- length(X, M), s(0) = s(M).   subcall
      X = [], M = 0                match 1
   ?- s(0) = s(0).                 match
   L = [_A];                       backtracks
      ...                          (1 fails)
```

Order of Conditions (4)

```
/*1*/ length([], 0).
/*2*/ length([_|X], N) :-
        length(X, M),
        N = s(M).
```

- Trace:

```
?- length(L, s(0)).
   L = [_A|X], N = s(0)            match 2
   ?- length(X, M), s(0) = s(M).   subcall
      X = [_B|X'], N = M           match 2
   ?- length(X', M'), M = s(M'),   subcall
      s(0) = s(M).
            ...
```

Order of Conditions (5)

- Program:

```
/*1*/ length([], 0).
/*2*/ length([_|X], N) :-
        N = s(M),
        length(X, M).
```

- Use:

```
?- length(L, s(0)).
L = [_A];

no
```

Declarative vs Procedural

- Order of clauses and conditions in clauses in Prolog progams may be changed, but
- This may be at the expense of:
  - loss of termination
  - compromised efficiency
- Schema for procedural programming:
  - special case first (top, left)
  - general case (e.g. including a recursive call) last (bottom, right)

Fail & Cut

- Notation: fail and !
- Control predicates: affect backtracking
- Used for:
  - efficiency reasons
  - implementing tricks

Enforcing Backtracking: fail

- ?- fail.
  no (no match)
- Program:

```
p(a).
p(b).
```

Query:

```
?- p(X).        (match)
X = a
yes
```

Fail - no Recursion

- Program:

```
p(a).
p(b).
p(X) :- q(X).
q(c).
```

- Query:

```
?- p(X), write(X), nl, fail.
a
b
c          backtracking
no
```

Fail - with Recursion

- Program:

```
/*1*/  member(X, [X|_]).
/*2*/  member(X, [_|Y]) :-
            member(X,Y).
```

- Query/call:

```
?- member(Z,[a,b]), write(Z), nl, fail.
   Z = X, X = a                match 1
?- write(a), nl, fail.
a              backtracking
?- member(Z,[a,b]), write(Z), nl, fail.
   Z = X, Y = [b]              match 2
```

Controlling Backtracking: !

- Procedural meaning of the cut !:

A :- B1, B2, !, B3, B4.

Search for alternatives

Search for alternatives

!

Stop searching

Cut

Program:

```
p(a).
p(b).
q(X) :- p(X), r(X).
r(Y) :- !, t(Y).
r(a).
t(c).
```

Execution:

```
?- q(Z).
   Z = X
?- p(X), r(X).
   X = a
?- r(a).
   Y = a
?- t(a).
   fail, no
   backtracking
   to r(a).
   Try X = b
```

State Space and !

```
a :- b, c.
a :- f, g.
  ...
b :- d, !, e.
b :- ... .
  ...
d.
```



Various Applications of !

- Cut as commitment operator:

if X < 3 then Y = 0
if X ≥ 3 and X < 6 then Y = 2
if X ≥ 6 then Y = 4

- Prolog:

```
t(X, 0) :- X < 3.
t(X, 2) :- X >= 3, X < 6.
t(X, 4) :- X >= 6.
```

Commitment Operator

- Cut as commitment operator:

```
/*1*/  t(X, 0) :- X < 3.
/*2*/  t(X, 2) :- X >= 3, X < 6.
/*3*/  t(X, 4) :- X >= 6.
```

- Execution trace:

```
?- t(1, Y), Y > 2.                 match 1
?- 1 < 3, 0 > 2.
?- 0 > 2.                          fail 1
?- 1 >= 3, 1 < 6, 1 > 2.           match 2
?-    ...                          fail 2
?- 1 >= 6, 4 > 2.   match 3, fail 3   ☹
```

Commitment Operator

- Cut as commitment operator:

```
/*1*/  t(X, 0) :- X < 3, !.
/*2*/  t(X, 2) :- X >= 3, X < 6, !.
/*3*/  t(X, 4) :- X >= 6.
```

- Execution trace:

```
?- t(1, Y), Y > 2.                 match 1
?- 1 < 3, !, 0 > 2.
?- !, 0 > 2.                       fail 1
no                                    ☺
```

Various Applications of !

- Cut used for removal of conditions:

  min(X, Y) is X if X ≤ Y
  min(X, Y) is Y if X > Y

- Prolog:

```
min(X, Y, X) :- X =< Y.
min(X, Y, Y) :- X > Y.
```

- Execution:

```
?- min(3, 5, Z).
?- 3 =< 5.                 match 1
Z = 3                      yes
```

Removal of Conditions

- Cut used for removal of conditions:

```
min(X, Y, Z) :-
      X =< Y, !,
      Z = X.
min(X, Y, Y).
```

- Execution:

```
?- min(3, 5, W).
?- 3 =< 5, !, W = 3.       match 1
W = 3                      yes
```

Removal of Conditions

- Cut used for removal of conditions:

```
min(X, Y, Z ⇒ X) :-
      X =< Y, !.
      Z = X.          why included?
min(X, Y, Y).
```

- Execution:

```
?- min(3, 5, 5).
                           fail 1, match 2
yes
```

Change in Meaning?

- Cut used for removal of conditions:

```
min(X, Y, Z) :-
      X =< Y,        (! omitted)
      Z = X.
min(X, Y, Y).
```

- Execution:

```
?- min(3, 5, W), W = 5.
?- 3 =< 5, 5 = 3, W = 5.   match 1
?- 5 = 3, W = 5.           fail
?- W = 5.   match 2 (with Y = 5 = W)
W = 5
yes
```

Negation by Failure

- Simulation of negation: not(p) is true if p is false (fails):

```
not(X) :- call(X), !, fail.
not(X).
```

- **Example:**

```
p(a).
q(X) :- p(X), not(r(X)).
r(c).
?- q(Y).
yes
```

Single Solution

- Circumvention of double search:

```
/*1*/  member(X, [X|_]) :- !.
/*2*/  member(X,[_|Y]) :-
          member(X,Y).
```

- **Example:**

```
?- member(a, [a, b, a]).
yes

?- member(X, [a, b]).
X = a;
no
```

Green and Red Cuts

- **Green cut:**
  - when omitted, does not change declarative (logical) meaning of program
  - used to increase efficiency
- **Red cut:**
  - when omitted, declarative meaning of program is changed
  - used for efficiency
  - used to enforce termination

Green and Red Cuts

- **Green cut:**
  - commitment operator
- **Red cut:**
  - removal of conditions
  - cut-fail combination (see notes)
  - single solution

Prolog Database

- The working environment of Prolog, containing all loaded Prolog programs is called: the 'database'
- The database can be manipulated by the programs themselves
- Compare: Pascal program that modifies itself during execution

Prolog 'Database'

add new clauses ⇨

remove clauses ⇦

Prolog Database

```
parent(jim, bob).

pred(X,Y) :-
    parent(X,Y).
pred(X,Y) :-
    parent(X,Z),
    pred(Z,Y).
```

Prolog 'Database'

assertz: add to the end of a definition

assertz(parent(bob,ann)).

Prolog Database

```
parent(jim, bob).
parent(bob,ann).
pred(X,Y) :-
    parent(X,Y).
pred(X,Y) :-
    parent(X,Z),
    pred(Z,Y).
```

Asserting Clauses

Database

```
collect_data(stop).
collect_data(_) :-
    write('Next item: '),
    read(X),
    assertz(X),
    collect_data(X).

input_data :-
    collect_data(start).
```

```
name(peter).
age(35).
stop.
```

```
?- input_data.
Next item: name(peter).
Next item: age(35).
Next item: stop.
```

Database Manipulation

- Asserting (new) clauses:
  - assert(C): position C unspecified
  - asserta(C): at the beginning of the definition of the predicate
  - assertz(C): at the end of the definition of the predicate
- Deleting clauses:
  - retract(C): remove clause matching with C (top to bottom order)

Retracting Clauses

retract: remove from the beginning of the of definition

```
?- retract(parent(X,Y)).
    X = jim
    Y = bob
yes
```

Prolog Database

```
?- dynamic parent/2.
parent(jim, bob).
parent(bob,ann).
parent(john,pete).
parent(pete,linda).
```

Retracting Clauses

```
?- retract_all_facts(parent(X,Y)).
yes
```

Prolog Database

```
?- dynamic parent/2.
parent(jim, bob).
parent(bob,ann).
parent(john,pete).
parent(pete,linda).

retract_all_facts(X) :-
    retract(X),
    fail.
retract_all_facts(_).
```